



METERING AND TRANSFERRING LIQUIDS

PRECISE, SAFE AND CLEAN HANDLING
OF NEUTRAL AND AGGRESSIVE LIQUIDS

LIQUIPORT®



RELIABLE

NF 100 and NF 300 Chemically-resistant Diaphragm Liquid Pump

- Flow rate from 0.2 up to 3 l/min / Pressure head 10 mWg, suction head 3 mWg
- Self priming, dry running
- Pump heads available in your choice of PP, PVDF or PTFE – diaphragms available in PTFE, valves in FFKM
- Pressure head also available for 40 mWg on request
- Flow rate can either be set manually (Version S) or both manually and via an external control device (Version RC)

SIMDOS®



PRECISE

SIMDOS® 02 and SIMDOS® 10 Chemically-resistant Diaphragm Liquid Pump

- Flow rate from 0.03 up to 100 ml/min / Pressure head max. 6 bar, suction head 2 mWg and 3 mWg respectively
- Pump heads available in your choice of PP, PVDF, PTFE – diaphragms available in FFKM or PTFE-coated respectively PTFE-coated only (SIMDOS 10), valves in FFKM
- Flow rate can either be set manually (Version S) or both manually and via an external control device as well as with interface RS 232 (Version RCP)
- Additional safety diaphragm for maximum security
- Easy exchange of the transfer diaphragm by activating the maintenance command in the operating program